

Medicool™ Undercounter Laboratory Refrigerator & Freezer

SR-L4110W
SR-L4110WSEC
HF-5017W
HF-5017WSEC

SANYO laboratory refrigerators and freezers are designed specifically for the demanding standards of clinical, life science, biotechnology and industrial laboratories.



SR-L4110W and SR-L4110WSEC

Medicool™ Laboratory Appliance Series Refrigerator

Laboratory Appliance series +4°C refrigeration for undercounter or free standing applications.

Chamber Features

The chamber features three adjustable full depth shelves and flat inner door liner for maximum storage capacity. The interior liner is fabricated from seamless high impact polystyrene with rounded corners for ease in cleaning.

Design

Designed for general purpose, clinical, life science, biotechnology, and industrial use.

Temperature Control

Equipped with an adjustable thermostat for approximate temperature performance range of 1°C to 10°C. (must be verified with separate thermometer).

Hasp Lock

Models are available with a hasp lock for secured storage requirements and designated by the suffix "SEC" (SR-L4110WSEC).

HF-5017W and HF-5017WSEC

Medicool™ Laboratory Appliance Series Freezer

Laboratory Appliance series -20°C freezing for undercounter or free standing applications.

Chamber Features

The chamber features two fixed, evaporator shelves for quick freezing. Inner door shelving allows for full utilization of storage. The interior liner is fabricated from seamless high impact polystyrene with rounded corners for ease in cleaning.

Design

Designed for general purpose, clinical, life science, biotechnology, and industrial use.

Temperature Control

Equipped with an adjustable thermostat for approximate temperature performance range of -20°C to -15°C (Must be verified with separate thermometer). The unit is manual defrost for steady temperature performance.

Hasp Lock

Models are available with a hasp lock for secured storage requirements and designated by the suffix "SEC" (HF-5017WSEC)

Preservation
My life. My work. My choice.

General Specifications

Model Number	SR-L4110W & SR-L4110WSEC*	HF-5017W & HF-5017WSEC*
Internal Capacity/Volume	4.9 cu.ft.	5.0 cu.ft.
Exterior Dimensions	33¾" H x 21⅜" W x 22¾" D	33⅜" H x 21⅜" W x 25⅜" D
Clearance Requirements	1" clearance required from top, 1" from sides, and 4" from back	1" clearance required from top, 1" from sides, and 4" from back
Refrigeration System	SANYO built components, R-134A HFC "Green" refrigerant, internal skin condenser	SANYO built components, R-134A HFC "Green" refrigerant, internal skin condenser
Temperature Control	Temperature control thermostat located inside chamber	Temperature control thermostat located inside chamber
Temperature Range	1°C to 10°C	-20°C to -15°C
Interior Storage	Flat inner door liner, three adjustable full depth shelves	Two fixed shelves with cooling coils in shelves
Defrost Method	Automatic	Manual
Door Swing	Right side hinge, door swing is field reversible	Right side hinge
Electrical Requirements	115V, 60Hz, 0.9A	115V, 60Hz, 1.1A
Shipping Weight	76 lbs.	79 lbs.

*SR-L4110WSEC has hasp lock

*HF-5017WSEC has hasp lock

SR-L4110W



HF-5017W



SANYO is committed to developing green technologies that provide energy efficiency resulting in lower operational costs with less impact on the environment.



SANYO North America Corporation
Biomedical and Environmental Solutions Division
1300 Michael Drive, Suite A, Wood Dale, IL 60191 USA
Toll Free USA 800-858-8442 • Fax 630-238-0074
www.sanyobiomedical.com

SANYO Canada, Inc.
201 Creditview Road, Woodbridge, Ontario L4L 9T1
905-265-4100 • Fax 905-265-4101