

PTB 111E – Manual Tablet Hardness Testing Instrument



The manual tablet hardness testing instrument **PTB 111E** is a **dual force mode** hardness test apparatus as it can be used for either linear force or linear speed increase while tablet hardness is tested. It offers a multiple point validation procedure for the built-in digital load cell.

The instrument is made in strict compliance with the **EP <2.9.8>** and **USP <1217>** Pharmacopoeia.

Enter the nominal test information for hardness as well as a batch number via the PTB 111E keyboard. Select the unit to measure, KP (Kilopond), N (Newton) or Sc (Strong Cobb), now place the sample onto the sample dish and start the test. The driven jaw will run forward, touch and force the tablet until it breaks to measure the hardness (tablet breaking force).

The result is immediately displayed and printed to a connected dot-matrix or suitable PCL5 type laser- or printer. Repeat this until your series has been tested, get a full print-out including each individual result, date, time, serial number of the instrument, batch number of the product tested, mean value and deviations of the test series.

The flexibility and the reproducibility of the results have made this and other models, like the PTB 311E series become one of the most sold tablet hardness testing instruments worldwide.

Operating Principle

Even in the existing USP and EP monographs there is no standard force setting or force increase mode established, but it is recommended to use a linear force increase rate of 20N/s. Different force settings usually cause problems when comparing results received by different supplier's instruments when testing the same tablet. The hardness result is directly influenced by the contact speed and force increase rate. Faster operated test jaw means lower reproducibility and often higher results. In order to offer the possibility to select an operating mode which will offer you similar results as the instruments you may already use, select the force mode, linear force increase or linear speed increase and select the same or similar rate. Also touch and detection force may be altered to suit the sample design specification. When the sample is touched the instrument switches to the selected mode and linear increasing rate.

Which Force Mode Should Be Selected?

For more than 18 years all Pharma Test hardness testing instruments offer the possibility to select either linear force or linear speed increase. Linear force increase is the recommended setting as it offers the most accurate control, as the rate of increase is directly controlled by the electronic load cell used to read the force. Also it is quite simple to validate the correct and linear operation as a tablet having a hardness of 100 Newton will be broken within 5 seconds if 20N/s had been set as force increase rate.

Linear speed increase can also be used. Here the driving speed of the motor is kept linear. Actually if the touching force is kept low there is not too much difference in results between the two systems but it is very difficult to validate the linearity of the drive speed.

Calibration and Validation

The current USP Pharmacopeia requires the force sensor of a tablet hardness testing instrument to be calibrated periodically over the complete measuring range (or the range used for measuring samples) with a precision of 1N. All Pharma Test tablet hardness testing instrument can be statically calibrated over the complete measuring range by the use of different traceable counterweights. All instruments support the checking of at least three different points during calibration to prove the linearity of the force sensor. Furthermore, Pharma Test offers the PT-MT magnetic tablets to calibrate the breakpoint detection of the whole tablet hardness testing instrument (force sensor and mechanics of the instrument). All Pharma Test tablet hardness testing instruments are fully compliant to the requirements of the current USP Pharmacopeia.



PT-MT3

The PTB 111E offers a built-in calibration and validation program for the hardness test station. To validate the hardness test station the PT-MT magnetic tablet or different certified weights are used. Use the PT-MT to qualify the correct breakpoint detection, the PT-MT instrument works like a tablet, it withstands force and after “breaks”.

For the two point adjustment (zero and reference) of the load cell inside the hardness station a certified reference weight of 10 kg is used. For validation purposes the use 5 up to 30kg certified weights is recommended. All adjustment and

calibration results can be printed and countersigned.

To prove the linearity of the instrument, the operator can program a print-out of the force curve recorded during a test. This will show the linear increase of the adjusted force mode. Also different weights, like the PTB-CAL15 and PTB-CAL30 which includes 5, 10, 15kg and also 30kg or the PTB-CAL30 using 2 additional 10kg weights for total 50kg, may be placed onto the load cell or the PT-MT shall be used to validate the linearity. Using the parallel port a Matrix or PCL5 printer can be added and using the RS232 COM port, all results can be transmitted to software running on a computer system.



PTB-CAL 30

Advantages

Some of the highlights the PTB 111E offers are:

- Select either linear force or linear speed increase (dual mode selection)
- Entry of time and date
- Enter a 12 digit batch number
- Automatic re-start facility to speed up the testing sequence
- Documentation of all results using a separate Dot-Matrix or PCL5 printer
- Validation and calibration program for the measurement station
- Force curve print out
- Dual point adjustment of the load cell for the hardness test station
- Multiple point validation (calibration)
- Programmable print-out of force increase curve
- Data transfer via RS-232 interface
- Hardness testing in compliance with the EP <2.9.8> and USP <1217> Pharmacopoeia
- Test program for soft gelatine capsule testing by setting up a testing distance

Features

The main features of the PTB 111E are:

- Fully USP <1217> and EP <2.9.8> compliant
- Dual force mode instrument with linear speed increase and linear force increase modes
- Multiple point validation procedure built-in
- Programmable print-out of force increase curve
- Set to test tension strength of oblongs and caplets available

Standard Scope of Supply

The PTB 111E comes ready to use with the following standard scope of supply:

- Standard Jaw set to allow hardness test of all size and shape samples
- Broken Sample collector
- Comprehensive documentation folder including:
 - User manual
 - IQ documentation
 - OQ documentation
 - Conformity Declaration
 - CE/EMC Declaration
 - Instrument logbook

Options

In addition to the standard scope of supply Pharma Test offers a broad range of accessories and options including:

- Tension test set to test break line force of shaped tablets
- 500N (PTB 111E-500) and 1000N (PTB 111E-1000) extended force range
- Recommended spare part set
- Full range of certified validation tools available



Tension Strength Test Set

Technical Data

Parameter	Specification
Display	LED Display showing number of tests and hardness result
Data Entry	Numerical and Functional keys
Standard Force Range	5.0 to approximately 300N
Accuracy	< 1N
Resolution	0.074N (300N model) - 0.1482N (500N model) - 0.2964N (1000N model)
Force Settings	Linear speed or linear force increase
Selectable Range	5.0 - 200 N/Second or Millimeter/Minute
Accuracy	< 2% force or < 0.1% speed
Maximum Sample Size	45 mm
Drive Way Setting	1.0 - 30.0 mm to adapt sample size
Printer	Interface to connect Dot-Matrix or PCL 5 Printer
Interface	RS232 COM port
Calibration Guidance	Built-in calibration procedures the digital load cell
Adjustments	Two point adjustment - zero and 10kg
Calibrations	Multiple point for load cell precision using certified weights (CAL15)
Force Detection	PT-MT Magnetic Tablet
Reproducibility	
Instrument Housing	Stainless Steel to meet GLP requirements
Bench Space Requirement	L 48cm x W 24cm x H 26cm (without external printer)
Certification	All components certified to USP / EP requirements
CE / EMC Certification	All CE / EMC Certification provided
Validation	All IQ & OQ documents included